

Transporters

specifications

Construction:

Unit is constructed using ¾" thick particle board with thermal-fused laminate on both sides with 1" TFL top over ¾" subtop. Fully finished back and all edges are finished using 3mm PVC edge banding.

Transporter Components:

Each unit has 4" heavy-duty casters for mobility (two locking; two non-locking). 1" thick adjustable shelf with anti-tip shelf clips. Offset five knuckle hinges allow the doors to completely swing open. Some units available with center divider, chrome garment rod and drawers with ¾" thermal-fused laminate and heavy-duty drawer glides.

Model Numbers:

MODEL NO	W X D	HGT	# OF SHELVES	WGT
SS5000-3660	36 X 24	60	3 ADJ / 1 FX	240
SS5000-4860	48 X 24	60	3 ADJ / 1 FX	271
SS5000-3672	36 X 24	72	4 ADJ / 1 FX	270
SS5000-4872	48 X 24	72	4 ADJ / 1 FX	345
SS5010-4860	48 X 24	60	6 ADJ / 2 F X	251
SS5010-4872	48 X 24	72	8 ADJ / 2 F X	360
SS5020-3660	36 X 24	60	4 ADJ / DIV / ROD	276
SS5020-4860	48 X 24	60	5 ADJ / DIV / ROD	285
SS5020-3672	36 X 24	72	4 ADJ / DIV / ROD	275
SS5020-4872	48 X 24	72	5 ADJ / DIV / ROD	360
SS5030-4872	48 X 24	72	3 ADJ / 4 DRWRS / ROD	420
SS5040-4860	48 X 24	60	2 ADJ / 2 DRWRS / ROD	286
SS5040-4872	48 X 24	72	2 ADJ / 2 DRWRS / ROD	375
SS5050-4872	48 X 24	72	20 TRAYS / FIXED SHELF / ROD	365



Tote Trays:

Models SS5000 - SS5040 - 12.25"W x 16.75"L x 2.75"H clear
Model SS5050 - 14.25"W x 19"L x 4.5"H Shirley K clear

Assembly:

Each unit is factory assembled using dowel construction.

Options:

Vertical wardrobe lock or integrated lock.

Shipping Class:

125

SS5000



SS5010



SS5020



SS5030



SS5040



SS5050



Specs subject to change.

V070714